

BANTEK RLP 110 Rubber liquid paint Weatherproof Exterior Emulsion is a high performance, long lasting exterior paint specially formulated to withstand extreme tropical conditions of high rainfall, humidity and heat.

Top

BANTEK RLP 110 Rubber liquid paint Weatherproof Exterior Emulsion is a 100% modified acrylic, anti-mildew, high performance exterior wall finish. It is based on a UV resistant acrylic binder and lightfast pigment. It has excellent water-repellent properties and excellent anti-microbial properties, inhibiting the growth of fungus and algae and helping to maintain the bright color year after year. We do not add lead, mercury, arsenic chromium and other raw materials containing heavy metals to the manufacturing process.

BANTEK RLP 110 Rubber liquid paint

BANTEK RLP 110 Rubber liquid paint Weatherproof Exterior Emulsion is an exterior wall finish that can be applied over various types of exterior cement plaster. External sealing, asbestos sheet, concrete etc. The product cannot be applied to surfaces/substrates that are subject to continuous seepage moisture.

#### HOW TO APPLY

BANTEK RLP 110 Rubber liquid paint Weatherproof Exterior Emulsion is a high performance, long lasting exterior paint specially formulated to withstand extreme tropical conditions of high rainfall, humidity and heat.

Top

BANTEK RLP 110 Rubber liquid paint Weatherproof Exterior Emulsion is a 100% modified acrylic, anti-mildew, high performance exterior wall finish. It is based on a UV resistant acrylic binder and lightfast pigment. It has excellent water-repellent properties and excellent anti-microbial properties, inhibiting the growth of fungus and algae and helping to maintain the bright color year after year. We do not add lead, mercury, arsenic chromium and other raw materials containing heavy metals to the manufacturing process.

Asian Paints

BANTEK RLP 110 Rubber liquid paint Weatherproof Exterior Emulsion is an exterior wall finish that can be applied over various types of exterior cement plaster. External sealing, asbestos sheet, concrete etc. The product cannot be applied to surfaces/substrates that are subject to continuous seepage/moisture.

#### ADDITIONAL INFORMATION

technical data

a) Coverage \*\*

Brushing 1st coat on normal primed masonry surface: 10.5 11.5 sq.mtr/tr (110-130 sq.ft/ltr) 2nd coat: 55 sq.mtr/ltr (55-67 sq.ft/ltr)

Surface drying time 30 minutes

b) drying time

c) Gloss Level / Sheen

d) flash point

(IS 101/1987. Part 1, Section 6)

2 11 at 60°GH

Not Applicable

**BANTEK RLP 110**

Tightly sealed 3 years from date of original manufacture

1) shelf life

container away from direct sunlight and heat

\*\*Actual coverage may differ from quoted coverage due to method of application and factors such as surface condition, roughness and porosity.

Darker bright colors may require additional coats of paint.

safety features

Store container with lid tightly closed in an upright position,

Keep out of reach of children and away from food and drink

Wear eye protection during application. In

rinse immediately with plenty of water and seek medical advice

skin

Together

Of water. Get

Do not breathe vapor or spray. it is

or remains

Nose pad during sanding and surface preparation to avoid dust

breathe.

Product: BANTEK PCP 115 Polymer crack putty



Use information

:  
:  
:  
:  
:  
:  
: